

Printing date 27.03.2020 Version: 5 Revision: 25.03.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

• Trade name: PEROXAN BCC-75

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance /

the mixture

Reaction initiator For industrial use

· 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: PERGAN GmbH

Hilfsstoffe für industrielle Prozesse

Schlavenhorst 71 D-46395 Bocholt Tel: +49 2871 9902-0 Fax: +49 2871 9902-50

Further information obtainable

from:

Environment protection / Security of labour

Competent person:

* Sales Manager Germany: Mr. Ansgar Pappenheim, e-mail: a.pappenheim@pergan.com * Export Sales Manager: Mr. Dr. Thomas Philipps, e-mail: dr.philipps@pergan.com * Environment protection / : Mr. Christoph Wilting, e-mail: c.wilting@pergan.com

Security of labour

· 1.4 Emergency telephone

number:

- Tel: +49 2871 9902-0

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Org. Perox. C H242 Heating may cause a fire.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to

Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



· Signal word Danger

· Hazard-determining

components of labelling:

di-(4-tert.-butylcyclohexyl)-peroxydicarbonate

Hazard statements H242 Heating may cause a fire.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P220 Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators

(e. g. heavy metal compounds and amines).

P234 Keep only in original packaging. P264 Wash thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.

P410 Protect from sunlight.

P411+P235 Store at temperatures not exceeding +30°C. Keep cool.
P420 Do not mix with peroxide-accelerators or reducing agents.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

----- GB ---



Printing date 27.03.2020 Version: 5 Revision: 25.03.2020

Trade name: PEROXAN BCC-75

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Dangerous components:		
	di-(4-tertbutylcyclohexyl)-peroxydicarbonate Org. Perox. C, H242; Skin Sens. 1, H317; Aquatic Chronic 3, H412	70-80%
	4-tert-butylcyclohexanol Eye Irrit. 2, H319	2.5-5%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information:

Take care of personal protection for the first aider.

· After inhalation: Take affected persons into fresh air and keep quiet.

· After skin contact: Immediately remove contaminated clothing.

· After eye contact: Rinse opened eye for several minutes under running water.

· After swallowing: If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delaved

4.3 Indication of any immediate medical attention and special

treatment needed

No further relevant information available

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

· Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from

the substance or mixture Under certain fire conditions, traces of other toxic gases cannot be excluded.

Hydrocarbons, carbondioxide and -monoxid.

5.3 Advice for firefighters

· Protective equipment: Do not inhale explosion gases or combustion gases. Additional information Cool endangered receptacles with water spray.

Self-protection first!

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

After exceeding the emergency temperature must be diluted with a suitable desentisation agent to < 10 %.

In case of further temperature should be cooled with waterspray from a safe distance.

Wear breathing apparatus with filter A during decomposition of materials.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:



Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Large quantities should be diluted with suitable desensitation agent to a concentration below 10 % before

disposal.

Pick up mechanically, collect in a suitable receptacle and dispose in accordance with government

regulations.

· 6.4 Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

In case of large spillage the environmental authority should be informed.

GB



Printing date 27.03.2020 Version: 5 Revision: 25.03.2020

Trade name: PEROXAN BCC-75

(Contd. of page 2)

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep receptacles tightly sealed.

Keep away from heat and direct sunlight. Open and handle receptacle with care.

Prevent formation of dust.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Do not refill residue into storage receptacles. Restrict the quantity stored at the work place.

Before break and at the end of work hands should be thoroughly washed. Only use tools made of suitable materials (e. g. polyethylene or stainless steel).

The product must be preserved, stored and transported continously cool.

Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-

metal compounds and amines). While using do not eat, drink or smoke. Do not generate flames or sparks

Keep product and emptied container away from heat and sources of ignition.

Avoid shock and friction.

Take precautionary measures against static discharges.



Do not smoke.

· Information about fire - and explosion protection:

Protect from heat.

Protect against electrostatic charges.

Prevent impact and friction

Use explosion-proof apparatus / fittings and spark-proof tools.

Dust can combine with air to form an explosive mixture.

Substance/product is oxidising when dry.

Product is not explosive. However, formation of explosive air/dust mixtures are possible.



Avoid open flames, sparks, direct sunlight and other sources of ignition.

Keep ignition sources away - Do not smoke.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

Pay attention to the special requirements of your local autorithies for storing dangerous goods.

Requirements to be met by storerooms and receptacles:

Store only in the original receptacle. Prevent any seepage into the ground.

Use only receptacles specifically permitted for this substance/product.

· Information about storage in one common storage facility:

Do not store or park organic peroxide together with heavy metal compounds and amines.

Store away from foodstuffs, drinks and feeding stuffs.

· Further information about storage conditions:

Keep container tightly sealed. Protect from heat and direct sunlight.

Protect from contamination.

Recommended storage temperature (To maintain

quality):

+5 +15 °C

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about

design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be

monitored at the workplace.

DNELs

15520-11-3 di-(4-tert.-butylcyclohexyl)-peroxydicarbonate

Dermal DNEL Longterm System 16.67 mg/kg bw/day (Worker)

Inhalative DNEL Longterm System 5.87 mg/m3 (Worker)

(Contd. on page 4)



Printing date 27.03.2020 Version: 5 Revision: 25.03.2020

Trade name: PEROXAN BCC-75

(Contd. of page 3)

· PNECs

15520-11-3 di-(4-tert.-butylcyclohexyl)-peroxydicarbonate

PNEC Marinewater sed PNEC Freshwater 0.39 mg/l (AF 100)
PNEC Freshwater sed PNEC Soil 936.8 mg/kg sed dw (-)
PNEC STP 2 mg/l (AF 10)
PNEC Marinewater 0.039 mg/l (AF 1.000)

· Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment:

· General protective and

hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection.

Be sure to clean skin thoroughly after work and before breaks.

Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer

exposure use self-contained respiratory protective device.

Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.



Filter P2

• Protection of hands: Only use chemical-protective gloves with CE-labelling of category III.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the

degradation

Protective gloves

• Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of

quality and varies from manufacturer to manufacturer.

Butyl rubber, BR

Fluorocarbon rubber (Viton) Nitrile rubber, NBR

Neoprene

Penetration time of glove

material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be

observed.

· Eye protection:

Tightly sealed goggles

· Body protection:



Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form:

 Colour:
 Odour:
 Odour threshold:

 DH-value:
 Like powder
 white - yellowish
 Characteristic
 Not determined.

· Change in condition

Melting point/freezing point: Not applicable.
 Initial boiling point and boiling range: Not applicable.

Flash point: Not applicable.
Flammability (solid, gas): May cause fire.

· Decomposition temperature: +40 °C (SADT)

(Contd. on page 5)



Printing date 27.03.2020 Version: 5 Revision: 25.03.2020

Trade name: PEROXAN BCC-75

(Contd. of page 4)

· Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/dust mixtures are possible.
· Explosion limits:	
Lower:	Not determined.
· Upper:	Not determined.
· Vapour pressure:	Not applicable.
· Density:	Not determined.
· Bulk density at 10 °C:	540 kg/m³
Relative density	Not determined.
Vapour density	Not applicable.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
· water:	Undetermined.
Partition coefficient: n-octanol	/water: not determined
· Viscosity:	
· Dynamic:	Not applicable.
· Kinematic:	Not applicable.
9.2 Other information	No further relevant information available.
· Active oxygen	2.9 - 3.1 %

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

10.2 Chemical stability Thermal decomposition /

conditions to be avoided: SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating

decomposition may occur with substance in the packaging as used in transport. A dangerous selfaccelerating decomposition reaction and, under certain circumstances, explosion or fire can be cause decomposition at and above the temperature. Contact with incompatible substances can cause

decomposition at or below the SADT.

No decomposition if used and stored according to specifications.

To avoid thermal decomposition do not overheat. · 10.3 Possibility of hazardous

reactions

· 10.4 Conditions to avoid

No further relevant information available.

· 10.5 Incompatible materials:

Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g.

heavy-metal compounds and amines).

Self-accelerating decomposition at SADT.

· 10.6 Hazardous decomposition

products:

Hydrocarbons, carbondioxide and -monoxid.

No hazardous decomposition products if used and stored according to specifications.

· Additional information: Emergency procedures will vary depending on conditions. The customer should have an emergency

response plane in place.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

 Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

15520-11-3 di-(4-tert.-butylcyclohexyl)-peroxydicarbonate

Oral LD50 >5,000 mg/kg (rattus)

98-52-2 4-tert-butylcyclohexanol

Oral LD50 4,200 mg/kg (rattus)

Primary irritant effect:

· Skin corrosion/irritation Based on available data, the classification criteria are not met.

· Serious eye damage/irritation Low irritant effect

Respiratory or skin

sensitisation May cause an allergic skin reaction. CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

· Germ cell mutagenicity Based on available data, the classification criteria are not met. · Carcinogenicity Based on available data, the classification criteria are not met. Reproductive toxicity Based on available data, the classification criteria are not met.

(Contd. on page 6)



(Contd. of page 5)

Printing date 27.03.2020 Version: 5 Revision: 25.03.2020

Trade name: PEROXAN BCC-75

· STOT-single exposure Based on available data, the classification criteria are not met. STOT-repeated exposure Based on available data, the classification criteria are not met.

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

15520-11-3 di-(4-tert.-butylcyclohexyl)-peroxydicarbonate

LC50 / 96h | 704 mg/l (oncorhynchus mykiss)

12.2 Persistence and

degradability

12.3 Bioaccumulative potential No further relevant information available. · 12.4 Mobility in soil No further relevant information available.

Additional ecological information:

 General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

No further relevant information available.

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage

system.

12.5 Results of PBT and vPvB assessment

· PBT: Not applicable. · vPvB: Not applicable.

 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

Recommendation



After diluting with a suitable inert solid material to 10 %, the product must be supplied to a special treatment (e. g. thermal utilization) under observance of all official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-Waste disposal key:

number

Uncleaned packaging:

Recommendation: This material and its container must be disposed of as hazardous waste.

SECTION 14: Transport information

· 14.1 UN-Number · ADR, IMDG	UN3114
· 14.2 UN proper shipping name · ADR	UN3114 ORGANIC PEROXIDE TYPE C, SOLID, TEMPEI

ERATURE

PEROXYDICARBONATE)

·IMDG ORGANIC PEROXIDE TYPE C, SOLID, TEMPERATURE CONTROLLED (DI-(4-tert.-BUTYLCYCLOHEXYL)-PEROXYDICARBONATE)

Χ

· 14.3 Transport hazard class(es)

· ADR



5.2 (P2) Organic peroxides. · Class · Label 5.2

· IMDG



5.2 Organic peroxides. Class

Label 5.2

· IATA

· Class

(Contd. on page 7)



Printing date 27.03.2020 Version: 5 Revision: 25.03.2020

Trade name: PEROXAN BCC-75

	(Contd. of page 6)
·Label	X
· 14.4 Packing group · ADR, IMDG	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
 14.6 Special precautions for user Hazard identification number (Kemler code): Stowage Category Stowage Code 	Warning: Organic peroxides D SW1 Protected from sources of heat.
· Segregation Code	SW3 Shall be transported under temperature control. SG35 Stow "separated from" SGG1-acids SG36 Stow "separated from" SGG18-alkalis.
· 14.7 Transport in bulk according to Annex II of Marpol IBC Code	and the Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	0 Code: E0 Not permitted as Excepted Quantity
· Transport category · Tunnel restriction code	1 D
· RID / GGVSEB:	no admission
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	0 Code: E0 Not permitted as Excepted Quantity
· IATA · Remarks:	no admission
· Control temperature: · Emergency temperature:	+30 °C +35 °C

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Qualifying quantity (tonnes) for the application of lower-tier

requirements 50 t

Qualifying quantity (tonnes) for the application of upper-tier

requirements 200 t

- · National regulations:
- · Other regulations, limitations and prohibitive regulations

· Please note: Take care of the respective local regulations.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

H242 Heating may cause a fire. · Relevant phrases

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

Department issuing SDS: Environment protection / Security of labour

· Contact: Tel: +49 2871 9902-0 E-mail: mail@pergan.com

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the

International Transport of Dangerous Goods by Rail)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage

of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

(Contd. on page 8)



Printing date 27.03.2020 Version: 5 Revision: 25.03.2020

Trade name: PEROXAN BCC-75

(Contd. of page 7)

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal concentration, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
VPVB: very Persistent and very Bioaccumulative
Org. Perox. C: Organic peroxides – Type C/D
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

·* Data compared to the previous version altered.

GB -