

SECTION 1: Identification of the substance/mixture and of the company/undertaking





- **1.1 Product identifier**
- **Trade name:** PEROXAN PA-50
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture**
Reaction initiator
For industrial use
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:** PERGAN GmbH
Hilfsstoffe für industrielle Prozesse
Schlavenhorst 71
D-46395 Bocholt
Tel: +49 2871 9902-0
Fax: +49 2871 9902-50
- **Further information obtainable from:** Environment protection / Security of labour
Competent person:
* Sales Manager Germany: Mr. Ansgar Pappenheim, e-mail: a.pappenheim@pergan.com
* Export Sales Manager: Mr. Dr. Thomas Philipps, e-mail: dr.philipps@pergan.com
* Environment protection / Security of labour : Mr. Christoph Wiltung, e-mail: c.wiltung@pergan.com
- **1.4 Emergency telephone number:** - Tel: +49 2871 9902-0

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 3	H226	Flammable liquid and vapour.
Org. Perox. C	H242	Heating may cause a fire.
Acute Tox. 3	H331	Toxic if inhaled.
Eye Irrit. 2	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.
Aquatic Chronic 2	H411	Toxic to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008** The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**

			
GHS02 GHS06 GHS08 GHS09			
- **Signal word** Danger
- **Hazard-determining components of labelling:** tert-butyl peracetate
Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated
- **Hazard statements** H226 Flammable liquid and vapour.
H242 Heating may cause a fire.
H331 Toxic if inhaled.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H304 May be fatal if swallowed and enters airways.
H411 Toxic to aquatic life with long lasting effects.
- **Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P220	Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy metal compounds and amines).
P234	Keep only in original packaging.
P243	Take action to prevent static discharges.
P264	Wash thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331	Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Trade name: **PEROXAN PA-50**

(Contd. of page 1)

P405	Store locked up.
P410	Protect from sunlight.
P411+P235	Store at temperatures not exceeding +10°C. Keep cool.
P420	Do not mix with peroxide-accelerators or reducing agents.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

- PBT: Not applicable.
- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Dangerous components:

CAS: 107-71-1	tert-butyl peracetate	50-60%
EINECS: 203-514-5	Flam. Liq. 3, H226; Org. Perox. C, H242; Acute Tox. 3, H331; Aquatic Chronic 2, H411; Eye Irrit. 2, H319; Skin Sens. 1, H317	
Reg-No.: 01-2120759514-49		
CAS: 93685-81-5	Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated	40-50%
EINECS: 297-629-8	Alternative CAS number: 13475-82-6	
Reg-No.: 01-2119490725-29	Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 4, H413	

- Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:



Take care of personal protection for the first aider.

· After inhalation:

Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
Take affected persons into fresh air and keep quiet.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.
Immediately remove contaminated clothing.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

- Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents:

Water with full jet

· 5.2 Special hazards arising from the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded.
Hydrocarbons, carbondioxide and -monoxid.

· 5.3 Advice for firefighters

· Protective equipment:

Do not inhale explosion gases or combustion gases.

· Additional information

Cool endangered receptacles with water spray.
Self-protection first!

SECTION 6: Accidental release measures


· 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.
In case of further temperature should be cooled with waterspray from a safe distance.
Wear breathing apparatus with filter A during decomposition of materials.
Wear protective equipment. Keep unprotected persons away.




(Contd. on page 3)

Trade name: **PEROXAN PA-50**

(Contd. of page 2)

- **6.2 Environmental precautions:**  Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
 - Dispose contaminated material as waste according to item 13.
 - Ensure adequate ventilation.
 - Large quantities should be diluted with suitable desensitisation agent to a concentration below 10 % before disposal.
 - Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government regulations.
- **6.4 Reference to other sections**
 - See Section 7 for information on safe handling.
 - See Section 8 for information on personal protection equipment.
 - See Section 13 for disposal information.
 - In case of large spillage the environmental authority should be informed.

* **SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling**
 - Keep away from heat and direct sunlight.
 - Open and handle receptacle with care.
 - Prevent formation of aerosols.
 - Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.
 - Do not refill residue into storage receptacles.
 - Restrict the quantity stored at the work place.
 - Before break and at the end of work hands should be thoroughly washed.
 - Only use tools made of suitable materials (e. g. polyethylene or stainless steel).
 - Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).
 - While using do not eat, drink or smoke.
 - Do not generate flames or sparks.
 - Keep product and emptied container away from heat and sources of ignition.
 - Avoid shock and friction.
 - Take precautionary measures against static discharges.
- **Information about fire - and explosion protection:**
 -  Do not smoke.
 - Protect from heat.
 - Protect against electrostatic charges.
 - Prevent impact and friction.
 - Use explosion-proof apparatus / fittings and spark-proof tools.
 - Fumes can combine with air to form an explosive mixture.
 -  Wear shoes with conductive soles.
 - Formation of flammable or explosive gas/air-mixtures is possible.
 -  Avoid open flames, sparks, direct sunlight and other sources of ignition.
 - Keep ignition sources away - Do not smoke.
- **7.2 Conditions for safe storage, including any incompatibilities**
 - **Storage:** Pay attention to the special requirements of your local authorities for storing dangerous goods.
 - **Requirements to be met by storerooms and receptacles:**
 - Store only in the original receptacle.
 - Prevent any seepage into the ground.
 - Use only receptacles specifically permitted for this substance/product.
 - **Information about storage in one common storage facility:**
 - Do not store or park organic peroxide together with heavy metal compounds and amines.
 - Store away from foodstuffs, drinks and feeding stuffs.
 - **Further information about storage conditions:**
 - Keep container tightly sealed.
 - Protect from heat and direct sunlight.
 - Protect from contamination.
 - Storage in a collecting room is required.
 - **Recommended storage temperature (To maintain quality):**
 - 15 +10 °C

(Contd. on page 4)
GB —

Trade name: **PEROXAN PA-50**

(Contd. of page 3)

· **7.3 Specific end use(s)** No further relevant information available.**SECTION 8: Exposure controls/personal protection**· **Additional information about design of technical facilities:** No further data; see item 7.· **8.1 Control parameters**· **Ingredients with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· **DNELs****107-71-1 tert-butyl peracetate**

Dermal	DNEL Longterm System	1 mg/kg bw/day (Worker)
Inhalative	DNEL Acute Local	13.4 mg/m ³ (Worker)
	DNEL Longterm System	4.46 mg/m ³ (Worker)

· **PNECs****107-71-1 tert-butyl peracetate**

PNEC Freshwater	0.004 mg/l (AF 1.000)
PNEC Freshwater sed	0.03 mg/kg sed dw (-)
PNEC Soil	0.0035 mg/kg soil dw (-)
PNEC STP	0.07 mg/l (AF 10)
PNEC Marinewater	0.0004 mg/l (AF 10.000)

· **Additional information:** The lists valid during the making were used as basis.· **8.2 Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.
 Store protective clothing separately.
 Avoid close or long term contact with the skin.
 Avoid contact with the eyes and skin.
 Do not eat, drink, smoke or sniff while working.
 Use skin protection cream for skin protection.
 Be sure to clean skin thoroughly after work and before breaks.

· **Respiratory protection:**

Not necessary if room is well-ventilated.
 Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.



Filter A2

· **Protection of hands:**

Only use chemical-protective gloves with CE-labelling of category III.



Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Protective gloves

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Butyl rubber, BR
 Fluorocarbon rubber (Viton)
 Nitrile rubber, NBR
 Neoprene

· **Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Tightly sealed goggles

· **Body protection:**

Protective work clothing

Trade name: **PEROXAN PA-50**

(Contd. of page 4)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties	
General Information	
Appearance:	
· Form:	Fluid
· Colour:	Colourless
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
Change in condition	
· Melting point/freezing point:	Not applicable.
· Initial boiling point and boiling range:	Not applicable.
· Flash point:	35 °C
· Flammability (solid, gas):	Not applicable.
· Decomposition temperature:	> +70 °C (SADT)
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
· Lower:	Not determined.
· Upper:	Not determined.
· Vapour pressure:	Not determined.
· Density at 20 °C:	0.835 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
Solubility in / Miscibility with	
· water:	Undetermined.
· Partition coefficient: n-octanol/water:	not determined
Viscosity:	
· Dynamic:	Not determined.
· Kinematic:	Not determined.
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity	No further relevant information available.
· 10.2 Chemical stability	
· Thermal decomposition / conditions to be avoided:	SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous self-accelerating decomposition reaction and, under certain circumstances, explosion or fire can be cause decomposition at and above the temperature. Contact with incompatible substances can cause decomposition at or below the SADT. No decomposition if used and stored according to specifications. To avoid thermal decomposition do not overheat.
· 10.3 Possibility of hazardous reactions	Self-accelerating decomposition at SADT.
· 10.4 Conditions to avoid	No further relevant information available.
· 10.5 Incompatible materials:	Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).
· 10.6 Hazardous decomposition products:	Hydrocarbons, carbon dioxide and -monoxid. No hazardous decomposition products if used and stored according to specifications.
· Additional information:	Emergency procedures will vary depending on conditions. The customer should have an emergency response plane in place.

SECTION 11: Toxicological information

11.1 Information on toxicological effects	
· Acute toxicity	Toxic if inhaled.

(Contd. on page 6)
GB

Trade name: **PEROXAN PA-50**

(Contd. of page 5)

· LD/LC50 values relevant for classification:		
Oral	LD50	3,843 mg/kg (rattus)
Dermal	LD50	7,136 mg/kg (cuniculosus)
Inhalative	LC50 / 4h	9.2 mg/l (rattus)
107-71-1 tert-butyl peracetate		
Oral	LD50	2,562 mg/kg (rattus)
Dermal	LD50	4,757 mg/kg (cuniculosus)
Inhalative	LC50 / 4h	6.1 mg/l (rattus)
93685-81-5 Hydrocarbons, C4, 1,3-butadiene-free, polyimd., triisobutylene fraction, hydrogenated		
Oral	LD50	>5,000 mg/kg (rattus)
· Primary irritant effect:		
· Skin corrosion/irritation	Based on available data, the classification criteria are not met.	
· Serious eye damage/irritation	Causes serious eye irritation.	
· Respiratory or skin sensitisation	May cause an allergic skin reaction.	
· CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)		
· Germ cell mutagenicity	Based on available data, the classification criteria are not met.	
· Carcinogenicity	Based on available data, the classification criteria are not met.	
· Reproductive toxicity	Based on available data, the classification criteria are not met.	
· STOT-single exposure	Based on available data, the classification criteria are not met.	
· STOT-repeated exposure	Based on available data, the classification criteria are not met.	
· Aspiration hazard	May be fatal if swallowed and enters airways.	

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:	
107-71-1 tert-butyl peracetate	
EC50 / 72h	6.4 mg/l (pseudokirchneriella subcapitata)
LC50 / 96h	39.6 mg/l (brachydanio rerio)
EC50 / 48h	4.31 mg/l (daphnia magna)
93685-81-5 Hydrocarbons, C4, 1,3-butadiene-free, polyimd., triisobutylene fraction, hydrogenated	
EC50 / 48h	>0.04 mg/l (daphnia)
IC50 / 72h	>0.04 mg/l (alga)
· 12.2 Persistence and degradability	
No further relevant information available.	
· 12.3 Bioaccumulative potential	
No further relevant information available.	
· 12.4 Mobility in soil	
No further relevant information available.	
· Additional ecological information:	
· General notes:	
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water	
Do not allow product to reach ground water, water course or sewage system.	
Danger to drinking water if even small quantities leak into the ground.	
· 12.5 Results of PBT and vPvB assessment	
· PBT:	
Not applicable.	
· vPvB:	
Not applicable.	
· 12.6 Other adverse effects	
No further relevant information available.	

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation



After diluting with a suitable desensitisation agent to 10 %, the solution must be supplied to a special treatment (e. g. thermal utilization) under observance of all official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Waste disposal key:

Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-number.

· Uncleaned packaging:

· Recommendation:

This material and its container must be disposed of as hazardous waste.

Trade name: **PEROXAN PA-50**

(Contd. of page 6)

SECTION 14: Transport information

· 14.1 UN-Number · ADR, IMDG, IATA	UN3103
· 14.2 UN proper shipping name · ADR · IMDG · IATA	UN3103 ORGANIC PEROXIDE TYPE C, LIQUID (tert-BUTYL PEROXYACETAT), ENVIRONMENTALLY HAZARDOUS ORGANIC PEROXIDE TYPE C, LIQUID (tert-BUTYL PEROXYACETAT), MARINE POLLUTANT ORGANIC PEROXIDE TYPE C, LIQUID (tert-BUTYL PEROXYACETAT)
· 14.3 Transport hazard class(es) · ADR · Class · Label	5.2 (P1) Organic peroxides. 5.2
· IMDG · Class · Label	5.2 Organic peroxides. 5.2
· IATA · Class · Label	5.2 Organic peroxides. 5.2
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · Stowage Category · Stowage Code · Segregation Code	Warning: Organic peroxides. - D SW1 Protected from sources of heat. SG35 Stow "separated from" SGG1-acids SG36 Stow "separated from" SGG18-alkalis.
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code	25 ml Code: E0 Not permitted as Excepted Quantity 1 D
· RID / GGVSEB:	like ADR
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	25 ml Code: E0 Not permitted as Excepted Quantity

Trade name: **PEROXAN PA-50**

(Contd. of page 7)

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 50 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **National regulations:**
- **Other regulations, limitations and prohibitive regulations**
- **Please note:** Take care of the respective local regulations.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
 - H226 Flammable liquid and vapour.
 - H242 Heating may cause a fire.
 - H304 May be fatal if swallowed and enters airways.
 - H317 May cause an allergic skin reaction.
 - H319 Causes serious eye irritation.
 - H331 Toxic if inhaled.
 - H411 Toxic to aquatic life with long lasting effects.
 - H413 May cause long lasting harmful effects to aquatic life.
- **Department issuing SDS:** Environment protection / Security of labour
- **Contact:**
 - Tel: +49 2871 9902-0
 - E-mail: mail@pergan.com
- **Abbreviations and acronyms:**
 - RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 - ICAO: International Civil Aviation Organisation
 - ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - IATA: International Air Transport Association
 - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - DNEL: Derived No-Effect Level (REACH)
 - PNEC: Predicted No-Effect Concentration (REACH)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative
 - Flam. Liq. 3: Flammable liquids – Category 3
 - Org. Perox. C: Organic peroxides – Type C/D
 - Acute Tox. 3: Acute toxicity - inhalation – Category 3
 - Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 - Skin Sens. 1: Skin sensitisation – Category 1
 - Asp. Tox. 1: Aspiration hazard – Category 1
 - Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
 - Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4
- *** Data compared to the previous version altered.**