




SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** PEROXAN PB-50 A
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture**
Reaction initiator
For industrial use
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:** PERGAN GmbH
Hilfsstoffe für industrielle Prozesse
Schlavenhorst 71
D-46395 Bocholt
Tel: +49 2871 9902-0
Fax: +49 2871 9902-50
- **Further information obtainable from:** Environment protection / Security of labour
Competent person:
* Sales Manager Germany: Mr. Ansgar Pappenheim, e-mail: a.pappenheim@pergan.com
* Export Sales Manager: Mr. Dr. Thomas Philipps, e-mail: dr.philipps@pergan.com
* Environment protection / Security of labour : Mr. Christoph Wiltling, e-mail: c.wiltling@pergan.com
- **1.4 Emergency telephone number:** - Tel: +49 2871 9902-0

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**

| | | |
|-------------------|------|--|
| Org. Perox. C | H242 | Heating may cause a fire. |
| Skin Irrit. 2 | H315 | Causes skin irritation. |
| Eye Irrit. 2 | H319 | Causes serious eye irritation. |
| Skin Sens. 1 | H317 | May cause an allergic skin reaction. |
| STOT SE 3 | H335 | May cause respiratory irritation. |
| Aquatic Acute 1 | H400 | Very toxic to aquatic life. |
| Aquatic Chronic 3 | H412 | Harmful to aquatic life with long lasting effects. |
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008** The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**

GHS02 GHS07 GHS09
- **Signal word** Danger
- **Hazard-determining components of labelling:** tert-butyl perbenzoate
4-hydroxy-4-methylpentan-2-one
2,4-Pentanedione, peroxide
- **Hazard statements** H242 Heating may cause a fire.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H410 Very toxic to aquatic life with long lasting effects.
- **Precautionary statements**

| | |
|----------------|---|
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P220 | Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy metal compounds and amines). |
| P234 | Keep only in original packaging. |
| P264 | Wash thoroughly after handling. |
| P273 | Avoid release to the environment. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P410 | Protect from sunlight. |
| P411+P235 | Store at temperatures not exceeding +30°C. Keep cool. |
| P420 | Do not mix with peroxide-accelerators or reducing agents. |

Trade name: **PEROXAN PB-50 A**

(Contd. of page 1)

P501

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

| · Dangerous components: | | |
|--|--|--------|
| CAS: 123-42-2 EINECS: 204-626-7 Index number: 603-016-00-1 Reg-No.: 01-2119473975-21 | 4-hydroxy-4-methylpentan-2-one Flam. Liq. 3, H226; Eye Irrit. 2, H319; STOT SE 3, H335 | 30-40% |
| CAS: 614-45-9 EINECS: 210-382-2 Reg-No.: 01-2119513317-46 | tert-butyl perbenzoate Org. Perox. C, H242; Aquatic Acute 1, H400; Acute Tox. 4, H332; Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 3, H412 | 25-30% |
| CAS: 37187-22-7 EINECS: 253-384-9 Reg-No.: 01-2119965139-28 | 2,4-Pentanedione, peroxide Alternative CAS number: 13784-51-5 Org. Perox. D, H242; Eye Irrit. 2, H319; Skin Sens. 1, H317 | 10-20% |
| CAS: 123-54-6 EINECS: 204-634-0 Index number: 606-029-00-0 Reg-No.: 01-2119458968-15 | pentane-2,4-dione Flam. Liq. 3, H226; Acute Tox. 3, H311; Acute Tox. 3, H331; Acute Tox. 4, H302 | 5-10% |
| CAS: 7722-84-1 EINECS: 231-765-0 Index number: 008-003-00-9 Reg-No.: 01-2119485845-22 | hydrogen peroxide solution Ox. Liq. 1, H271; Skin Corr. 1A, H314; Acute Tox. 4, H302; Acute Tox. 4, H332; STOT SE 3, H335; Aquatic Chronic 3, H412 | 1-2.5% |

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- **General information:** Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.



Take care of personal protection for the first aider.

- **After inhalation:** Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
Take affected persons into fresh air and keep quiet.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
Immediately remove contaminated clothing.
- **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture** Under certain fire conditions, traces of other toxic gases cannot be excluded.
Hydrocarbons, carbondioxide and -monoxid.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.
Do not inhale explosion gases or combustion gases.
- **Additional information** Cool endangered receptacles with water spray.

(Contd. on page 3)

Trade name: **PEROXAN PB-50 A**

Self-protection first!

(Contd. of page 2)

SECTION 6: Accidental release measures**· 6.1 Personal precautions, protective equipment and emergency procedures**

Keep away from ignition sources.
In case of further temperature should be cooled with waterspray from a safe distance.
Wear breathing apparatus with filter A during decomposition of materials.
Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.



Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Large quantities should be diluted with suitable desensitisation agent to a concentration below 10 % before disposal.
Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government regulations.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
In case of large spillage the environmental authority should be informed.

*** SECTION 7: Handling and storage****· 7.1 Precautions for safe handling**

Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.
Do not refill residue into storage receptacles.
Restrict the quantity stored at the work place.
Use only in well ventilated areas.
Before break and at the end of work hands should be thoroughly washed.
Only use tools made of suitable materials (e. g. polyethylene or stainless steel).
Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).
While using do not eat, drink or smoke.
Do not generate flames or sparks.
Keep product and emptied container away from heat and sources of ignition.
Avoid shock and friction.
Take precautionary measures against static discharges.



Do not smoke.

· Information about fire - and explosion protection:

Protect from heat.
Protect against electrostatic charges.
Prevent impact and friction.
Use explosion-proof apparatus / fittings and spark-proof tools.
Fumes can combine with air to form an explosive mixture.



Wear shoes with conductive soles.

Formation of flammable or explosive gas/air-mixtures is possible.



Avoid open flames, sparks, direct sunlight and other sources of ignition.

Keep ignition sources away - Do not smoke.

· 7.2 Conditions for safe storage, including any incompatibilities**· Storage:**

Pay attention to the special requirements of your local authorities for storing dangerous goods.

· Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.
Prevent any seepage into the ground.
Use only receptacles specifically permitted for this substance/product.

(Contd. on page 4)

GB

Trade name: **PEROXAN PB-50 A**

(Contd. of page 3)

- **Information about storage in one common storage facility:** Do not store or park organic peroxide together with heavy metal compounds and amines. Store away from foodstuffs, drinks and feeding stuffs.
- **Further information about storage conditions:** Keep container tightly sealed.
Protect from heat and direct sunlight.
Protect from contamination.
Storage in a collecting room is required.
- **Recommended storage temperature (To maintain quality):** 0 +30 °C
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

· **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

123-42-2 4-hydroxy-4-methylpentan-2-one

| | |
|---------------------|---|
| WEL (Great Britain) | Short-term value: 362 mg/m ³ , 75 ppm Long-term value: 241 mg/m ³ , 50 ppm |
|---------------------|---|

7722-84-1 hydrogen peroxide solution

| | |
|---------------------|---|
| WEL (Great Britain) | Short-term value: 2.8 mg/m ³ , 2 ppm Long-term value: 1.4 mg/m ³ , 1 ppm |
|---------------------|---|

· **DNELs**

123-42-2 4-hydroxy-4-methylpentan-2-one

| | | |
|------------|----------------------|---------------------------------|
| Dermal | DNEL Longterm System | 840 mg/kg bw/day (Worker) |
| Inhalative | DNEL Longterm System | 59.2 mg/m ³ (Worker) |

614-45-9 tert-butyl perbenzoate

| | | |
|------------|----------------------|------------------------------|
| Dermal | DNEL Longterm System | 6.25 mg/kg bw/day (Worker) |
| Inhalative | DNEL Longterm System | 4 mg/m ³ (Worker) |

37187-22-7 2,4-Pentanedione, peroxide

| | | |
|------------|----------------------|----------------------------------|
| Dermal | DNEL Longterm System | 13.33 mg/kg bw/day (Worker) |
| Inhalative | DNEL Longterm System | 11.75 mg/m ³ (Worker) |

123-54-6 pentane-2,4-dione

| | | |
|------------|----------------------|-------------------------------|
| Dermal | DNEL Longterm System | 12 mg/kg bw/day (Worker) |
| Inhalative | DNEL Longterm System | 84 mg/m ³ (Worker) |

7722-84-1 hydrogen peroxide solution

| | | |
|------------|---------------------|--------------------------------|
| Inhalative | DNEL Longterm Local | 1.4 mg/m ³ (Worker) |
|------------|---------------------|--------------------------------|

· **PNECs**

123-42-2 4-hydroxy-4-methylpentan-2-one

| | |
|----------------------|--------------------|
| PNEC Marinewater sed | 0.91 mg/kg sed dw |
| PNEC Freshwater | 2 mg/l (AF 50) |
| PNEC Freshwater sed | 9.06 mg/kg sed dw |
| PNEC Soil | 0.63 mg/kg soil dw |
| PNEC STP | 10 mg/l (AF 100) |
| PNEC Marinewater | 0.2 mg/l (AF 500) |

614-45-9 tert-butyl perbenzoate

| | |
|----------------------|-----------------------|
| PNEC Marinewater sed | 0.024 mg/kg sed dw |
| PNEC Freshwater | 0.0088 mg/l (AF 50) |
| PNEC Freshwater sed | 0.24 mg/kg sed dw |
| PNEC Soil | 0.043 mg/kg soil dw |
| PNEC STP | 0.6 mg/l (AF 10) |
| PNEC Marinewater | 0.00088 mg/l (AF 500) |

37187-22-7 2,4-Pentanedione, peroxide

| | |
|----------------------|------------------------|
| PNEC Marinewater sed | 0.153 mg/kg sed dw (-) |
| PNEC Freshwater | 0.17 mg/l (AF 10) |
| PNEC Freshwater sed | 1.53 mg/kg sed dw (-) |

(Contd. on page 5)

Trade name: PEROXAN PB-50 A

(Contd. of page 4)

| | |
|---|-----------------------|
| PNEC Soil | 0.2 mg/kg soil dw (-) |
| PNEC STP | 6.2 mg/l (AF 10) |
| PNEC Marinewater | 0.017 mg/l (AF 100) |
| 123-54-6 pentane-2,4-dione | |
| PNEC Marinewater sed | 0.191 mg/kg sed dw |
| PNEC Freshwater | 0.2 mg/l (AF 50) |
| PNEC Freshwater sed | 1.909 mg/kg sed dw |
| PNEC STP | 1.32 mg/l (AF 10) |
| PNEC Marinewater | 0.02 mg/l (AF 500) |
| 7722-84-1 hydrogen peroxide solution | |
| PNEC Marinewater sed | 0.047 mg/kg sed dw |
| PNEC Freshwater | 0.013 mg/l (AF 50) |
| PNEC Freshwater sed | 0.047 mg/kg sed dw |
| PNEC Soil | 0.002 mg/kg soil dw |
| PNEC STP | mg/l (AF 100) |
| PNEC Marinewater | 0.013 mg/l (AF 50) |

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid close or long term contact with the skin.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Use skin protection cream for skin protection.

Be sure to clean skin thoroughly after work and before breaks.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.



Filter A2

· **Protection of hands:**

Only use chemical-protective gloves with CE-labelling of category III.



Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Protective gloves

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Butyl rubber, BR

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

Neoprene

· **Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

· **Body protection:**



Protective work clothing

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

- **Form:** Fluid
- **Colour:** colourless - yellowish
- **Odour:** Characteristic

(Contd. on page 6)

Trade name: **PEROXAN PB-50 A**

(Contd. of page 5)

| | |
|--|---|
| · Odour threshold: | Not determined. |
| · pH-value: | Not determined. |
| · Change in condition | |
| · Melting point/freezing point: | Not applicable. |
| · Initial boiling point and boiling range: | Not applicable. |
| · Flash point: | > SADT |
| · Flammability (solid, gas): | Not applicable. |
| · Decomposition temperature: | > +60 °C (SADT) |
| · Auto-ignition temperature: | Product is not selfigniting. |
| · Explosive properties: | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| · Explosion limits: | |
| · Lower: | Not determined. |
| · Upper: | Not determined. |
| · Vapour pressure: | Not determined. |
| · Density at 20 °C: | 1.05 g/cm ³ |
| · Relative density | Not determined. |
| · Vapour density | Not determined. |
| · Evaporation rate | Not determined. |
| · Solubility in / Miscibility with | |
| · water: | Undetermined. |
| · Partition coefficient: n-octanol/water: | not determined |
| · Viscosity: | |
| · Dynamic at 20 °C: | 15 mPas |
| · Kinematic: | Not determined. |
| · 9.2 Other information | No further relevant information available. |
| · Active oxygen | 4.7 - 5.0 % |

SECTION 10: Stability and reactivity

| | |
|---|---|
| · 10.1 Reactivity | No further relevant information available. |
| · 10.2 Chemical stability | |
| · Thermal decomposition / conditions to be avoided: | SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous self-accelerating decomposition reaction and, under certain circumstances, explosion or fire can be cause decomposition at and above the temperature. Contact with incompatible substances can cause decomposition at or below the SADT. No decomposition if used and stored according to specifications. To avoid thermal decomposition do not overheat. |
| · 10.3 Possibility of hazardous reactions | Self-accelerating decomposition at SADT. |
| · 10.4 Conditions to avoid | No further relevant information available. |
| · 10.5 Incompatible materials: | Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines). |
| · 10.6 Hazardous decomposition products: | Hydrocarbons, carbon dioxide and -monoxid. No hazardous decomposition products if used and stored according to specifications. |
| · Additional information: | Emergency procedures will vary depending on conditions. The customer should have an emergency response plane in place. |

SECTION 11: Toxicological information

| | |
|---|---|
| · 11.1 Information on toxicological effects | |
| · Acute toxicity | Based on available data, the classification criteria are not met. |

· LD/LC50 values relevant for classification:

123-42-2 4-hydroxy-4-methylpentan-2-one

| | | |
|--------|------|----------------------------|
| Oral | LD50 | 2,520 mg/kg (rattus) |
| Dermal | LD50 | 13,630 mg/kg (cuniculosus) |

(Contd. on page 7)

Trade name: **PEROXAN PB-50 A**

(Contd. of page 6)

| 614-45-9 tert-butyl perbenzoate | | |
|--|-----------|-----------------------|
| Oral | LD50 | 4,838 mg/kg (rattus) |
| Dermal | LD50 | 3,817 mg/kg (rattus) |
| Inhalative | LC100 4h | 4.9 mg/l (rattus) |
| | LC0 / 4h | 1.01 mg/l (rattus) |
| 37187-22-7 2,4-Pentanedione, peroxide | | |
| Oral | LD50 | >2,000 mg/kg (rattus) |
| Dermal | LD0 | >2,000 mg/kg (rattus) |
| 123-54-6 pentane-2,4-dione | | |
| Oral | LD50 | 575 mg/kg (rattus) |
| Dermal | LD50 | 790 mg/kg (rattus) |
| Inhalative | LC50 / 4h | 5.1 mg/l (rattus) |

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

123-54-6 pentane-2,4-dione

| | |
|------------|-------------------------------|
| LC50 / 96h | 72 mg/l (oncorhynchus mykiss) |
| EC50 / 48h | 75 mg/l (daphnia magna) |

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Very toxic for fish
- **Additional ecological information:**
- **General notes:** Also poisonous for fish and plankton in water bodies.
Very toxic for aquatic organisms
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation



After diluting with a suitable desensitisation agent to 10 %, the solution must be supplied to a special treatment (e. g. thermal utilization) under observance of all official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Waste disposal key:

Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-number.

(Contd. on page 8)

GB

Trade name: **PEROXAN PB-50 A**

(Contd. of page 7)

- **Uncleaned packaging:**
- **Recommendation:** This material and its container must be disposed of as hazardous waste.

SECTION 14: Transport information

| | |
|--|--|
| · 14.1 UN-Number · ADR, IMDG, IATA | UN3103 |
| · 14.2 UN proper shipping name · ADR · IMDG · IATA | UN3103 ORGANIC PEROXIDE TYPE C, LIQUID (tert-BUTYL PEROXYBENZOATE, ACETYL ACETONE PEROXIDE), ENVIRONMENTALLY HAZARDOUS ORGANIC PEROXIDE TYPE C, LIQUID (tert-BUTYL PEROXYBENZOATE, ACETYL ACETONE PEROXIDE), MARINE POLLUTANT ORGANIC PEROXIDE TYPE C, LIQUID (tert-BUTYL PEROXYBENZOATE, ACETYL ACETONE PEROXIDE) |
| · 14.3 Transport hazard class(es) · ADR · Class · Label | 5.2 (P1) Organic peroxides. 5.2 |
| · IMDG · Class · Label | 5.2 Organic peroxides. 5.2 |
| · IATA · Class · Label | 5.2 Organic peroxides. 5.2 |
| · 14.4 Packing group · ADR, IMDG, IATA | Void |
| · 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR): | Product contains environmentally hazardous substances: tert-BUTYL PEROXYBENZOATE Yes Symbol (fish and tree) Symbol (fish and tree) |
| · 14.6 Special precautions for user · Hazard identification number (Kemler code): · Stowage Category · Stowage Code · Segregation Code | Warning: Organic peroxides. - D SW1 Protected from sources of heat. SG35 Stow "separated from" SGG1-acids SG36 Stow "separated from" SGG18-alkalis. |
| · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |
| · Transport/Additional information: · ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code · RID / GGVSEB: | 25 ml Code: E0 Not permitted as Excepted Quantity 1 D like ADR |

(Contd. on page 9)
GB

Trade name: **PEROXAN PB-50 A**

(Contd. of page 8)

| | |
|-----------------------------------|--|
| · IMDG | |
| · Limited quantities (LQ) | 25 ml |
| · Excepted quantities (EQ) | Code: E0 Not permitted as Excepted Quantity |

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 50 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **National regulations:**
- **Other regulations, limitations and prohibitive regulations**
- **Please note:** Take care of the respective local regulations.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
 - H226 Flammable liquid and vapour.
 - H242 Heating may cause a fire.
 - H271 May cause fire or explosion; strong oxidiser.
 - H302 Harmful if swallowed.
 - H311 Toxic in contact with skin.
 - H314 Causes severe skin burns and eye damage.
 - H315 Causes skin irritation.
 - H317 May cause an allergic skin reaction.
 - H319 Causes serious eye irritation.
 - H331 Toxic if inhaled.
 - H332 Harmful if inhaled.
 - H335 May cause respiratory irritation.
 - H400 Very toxic to aquatic life.
 - H412 Harmful to aquatic life with long lasting effects.
- **Department issuing SDS:** Environment protection / Security of labour
- **Contact:** Tel: +49 2871 9902-0
E-mail: mail@pergan.com
- **Abbreviations and acronyms:**
 - RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 - ICAO: International Civil Aviation Organisation
 - ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - IATA: International Air Transport Association
 - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - DNEL: Derived No-Effect Level (REACH)
 - PNEC: Predicted No-Effect Concentration (REACH)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative
 - Flam. Liq. 3: Flammable liquids – Category 3
 - Ox. Liq. 1: Oxidizing liquids – Category 1
 - Org. Perox. C: Organic peroxides – Type C/D
 - Org. Perox. D: Organic peroxides – Type C/D
 - Acute Tox. 3: Acute toxicity - dermal – Category 3
 - Acute Tox. 4: Acute toxicity - inhalation – Category 4
 - Skin Corr. 1A: Skin corrosion/irritation – Category 1A
 - Skin Irrit. 2: Skin corrosion/irritation – Category 2
 - Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 - Skin Sens. 1: Skin sensitisation – Category 1
 - STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 - Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
 - Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

(Contd. on page 10)

Trade name: **PEROXAN PB-50 A**

(Contd. of page 9)

· * Data compared to the
previous version altered.