





## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** PEROXAN A-50 M
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture**  
Reaction initiator  
For industrial use
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:** PERGAN GmbH  
Hilfsstoffe für industrielle Prozesse  
Schlavenhorst 71  
D-46395 Bocholt  
Tel: +49 2871 9902-0  
Fax: +49 2871 9902-50
- **Further information obtainable from:** Environment protection / Security of labour  
Competent person:  
\* Sales Manager Germany: Mr. Ansgar Pappenheim, e-mail: a.pappenheim@pergan.com  
\* Export Sales Manager: Mr. Dr. Thomas Philipps, e-mail: dr.philipps@pergan.com  
\* Environment protection / : Mr. Christoph Wiltling, e-mail: c.wiltling@pergan.com  
Security of labour
- **1.4 Emergency telephone number:** - Tel: +49 2871 9902-0

## SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**

|                   |      |  |
|-------------------|------|--|
| Org. Perox. D     | H242 | Heating may cause a fire.                          |
| Acute Tox. 4      | H332 | Harmful if inhaled.                                |
| Skin Corr. 1C     | H314 | Causes severe skin burns and eye damage.           |
| Eye Dam. 1        | H318 | Causes serious eye damage.                         |
| Skin Sens. 1      | H317 | May cause an allergic skin reaction.               |
| Muta. 2           | H341 | Suspected of causing genetic defects.              |
| STOT SE 3         | H335 | May cause respiratory irritation.                  |
| Aquatic Chronic 3 | H412 | Harmful to aquatic life with long lasting effects. |
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008** The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**

GHS02 GHS05 GHS07 GHS08
- **Signal word** Danger
- **Hazard-determining components of labelling:** tert-butyl hydroperoxide  
4-hydroxy-4-methylpentan-2-one  
2,4-Pentanedione, peroxide  
pentane-2,4-dione
- **Hazard statements**

H242 Heating may cause a fire.  
H332 Harmful if inhaled.  
H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.  
H341 Suspected of causing genetic defects.  
H335 May cause respiratory irritation.  
H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements**

|      |   |
|------|---|
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  |
| P220 | Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy metal compounds and amines). |
| P234 | Keep only in original packaging.  |
| P243 | Take action to prevent static discharges.   |
| P264 | Wash thoroughly after handling.   |
| P273 | Avoid release to the environment.   |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.   |

Trade name: **PEROXAN A-50 M**

(Contd. of page 1)

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P405 Store locked up.

P410 Protect from sunlight.

P411+P235 Store at temperatures not exceeding +25°C. Keep cool.

P420 Do not mix with peroxide-accelerators or reducing agents.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

**SECTION 3: Composition/information on ingredients**

· **3.2 Chemical characterisation: Mixtures**

· **Dangerous components:**

|  |   |        |
|--|---|--------|
| CAS: 123-42-2<br>EINECS: 204-626-7<br>Index number: 603-016-00-1<br>Reg-No.: 01-2119473975-21  | 4-hydroxy-4-methylpentan-2-one<br>Flam. Liq. 3, H226; Eye Irrit. 2, H319; STOT SE 3, H335   | 50-60% |
| CAS: 37187-22-7<br>EINECS: 253-384-9<br>Reg-No.: 01-2119965139-28                              | 2,4-Pentanedione, peroxide<br>Alternative CAS number: 13784-51-5<br>Org. Perox. D, H242; Eye Irrit. 2, H319; Skin Sens. 1, H317   | 20-25% |
| CAS: 75-91-2<br>EINECS: 200-915-7<br>Reg-No.: 01-2119446670-40                                 | tert-butyl hydroperoxide<br>Flam. Liq. 3, H226; Org. Perox. F, H242; Acute Tox. 3, H311; Acute Tox. 2, H330; Muta. 2, H341; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Skin Sens. 1A, H317 | 10-20% |
| CAS: 123-54-6<br>EINECS: 204-634-0<br>Index number: 606-029-00-0<br>Reg-No.: 01-2119458968-15  | pentane-2,4-dione<br>Flam. Liq. 3, H226; Acute Tox. 3, H311; Acute Tox. 3, H331; Acute Tox. 4, H302   | 1-2,5% |
| CAS: 7722-84-1<br>EINECS: 231-765-0<br>Index number: 008-003-00-9<br>Reg-No.: 01-2119485845-22 | hydrogen peroxide solution<br>Ox. Liq. 1, H271; Skin Corr. 1A, H314; Acute Tox. 4, H302; Acute Tox. 4, H332; STOT SE 3, H335; Aquatic Chronic 3, H412   | 1-2,5% |

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures**

· **4.1 Description of first aid measures**

· **General information:** Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.



Take care of personal protection for the first aider.

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.  
Take affected persons into fresh air and keep quiet.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.  
Immediately remove contaminated clothing.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:**

If symptoms persist consult doctor.

· **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.


Trade name: **PEROXAN A-50 M**

(Contd. of page 2)


**SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture**  
Under certain fire conditions, traces of other toxic gases cannot be excluded.  
Hydrocarbons, carbondioxide and -monoxid.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.  
Do not inhale explosion gases or combustion gases.
- **Additional information**  
Cool endangered receptacles with water spray.  
Self-protection first!

**SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Keep away from ignition sources.  
In case of further temperature should be cooled with waterspray from a safe distance.  
Wear breathing apparatus with filter A during decomposition of materials.  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Inform respective authorities in case of seepage into water course or sewage system.  
 Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.  
Large quantities should be diluted with suitable desensitisation agent to a concentration below 10 % before disposal.  
Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government regulations.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.  
In case of large spillage the environmental authority should be informed.

**\* SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling**  
Keep receptacles tightly sealed.  
Store in cool, dry place in tightly closed receptacles.  
Keep away from heat and direct sunlight.  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Prevent formation of aerosols.  
Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.  
Do not refill residue into storage receptacles.  
Restrict the quantity stored at the work place.  
Use only in well ventilated areas.  
Before break and at the end of work hands should be thoroughly washed.  
Only use tools made of suitable materials (e. g. polyethylene or stainless steel).  
Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).  
Avoid contact with skin and eyes.  
While using do not eat, drink or smoke.  
Do not generate flames or sparks.  
Keep product and emptied container away from heat and sources of ignition.  
Avoid shock and friction.  
Take precautionary measures against static discharges.  
 Do not smoke.
- **Information about fire - and explosion protection:**  
Protect from heat.  
Protect against electrostatic charges.  
Prevent impact and friction.  
Use explosion-proof apparatus / fittings and spark-proof tools.

(Contd. on page 4)

MT

Trade name: **PEROXAN A-50 M**

(Contd. of page 3)

Fumes can combine with air to form an explosive mixture.



Wear shoes with conductive soles.

Formation of flammable or explosive gas/air-mixtures is possible.



Avoid open flames, sparks, direct sunlight and other sources of ignition.

Keep ignition sources away - Do not smoke.

**7.2 Conditions for safe storage, including any incompatibilities**

- **Storage:** Pay attention to the special requirements of your local authorities for storing dangerous goods.
- **Requirements to be met by storerooms and receptacles:**
  - Store in a cool location.
  - Store only in the original receptacle.
  - Prevent any seepage into the ground.
  - Use only receptacles specifically permitted for this substance/product.
- **Information about storage in one common storage facility:** Do not store or park organic peroxide together with heavy metal compounds and amines. Store away from foodstuffs, drinks and feeding stuffs.
- **Further information about storage conditions:**
  - Keep container tightly sealed.
  - Store in cool, dry conditions in well sealed receptacles.
  - Protect from heat and direct sunlight.
  - Protect from contamination.
  - Store in a cool place.
  - Storage in a collecting room is required.
- **Recommended storage temperature (To maintain quality):** +5 .... +25 °C
- **Storage class:** 5.2
- **7.3 Specific end use(s)** No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

- **Additional information about design of technical facilities:** No further data; see item 7.

**8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

**123-42-2 4-hydroxy-4-methylpentan-2-one**

WEL (Great Britain) Short-term value: 362 mg/m<sup>3</sup>, 75 ppm  
Long-term value: 241 mg/m<sup>3</sup>, 50 ppm

**7722-84-1 hydrogen peroxide solution**

WEL (Great Britain) Short-term value: 2,8 mg/m<sup>3</sup>, 2 ppm  
Long-term value: 1,4 mg/m<sup>3</sup>, 1 ppm

**DNELs**

**123-42-2 4-hydroxy-4-methylpentan-2-one**

Dermal DNEL Longterm System 840 mg/kg bw/day (Worker)  
Inhalative DNEL Longterm System 59,2 mg/m<sup>3</sup> (Worker)

**37187-22-7 2,4-Pentanedione, peroxide**

Dermal DNEL Longterm System 13,33 mg/kg bw/day (Worker)  
Inhalative DNEL Longterm System 11,75 mg/m<sup>3</sup> (Worker)

**75-91-2 tert-butyl hydroperoxide**

|                     |                      |                                   |
|---------------------|----------------------|-----------------------------------|
| Oral                | DNEL Longterm System | 0,26 mg/kg bw/day (Comsumer)      |
| Dermal              | DNEL Longterm System | 12,5 mg/kg bw/day (Worker)        |
|                     |                      | 7,5 mg/kg bw/day (Comsumer)       |
| Inhalative          | DNEL Acute Systemic  | 10,4 mg/m <sup>3</sup> (Worker)   |
|                     |                      | 3,2 mg/m <sup>3</sup> (Comsumer)  |
|                     | DNEL Acute Local     | 21,3 mg/m <sup>3</sup> (Worker)   |
|                     |                      | 12,8 mg/m <sup>3</sup> (Comsumer) |
|                     | DNEL Longterm System | 3,1 mg/m <sup>3</sup> (Worker)    |
|                     |                      | 0,91 mg/m <sup>3</sup> (Comsumer) |
| DNEL Longterm Local |                      | 0,83 mg/m <sup>3</sup> (Worker)   |
|                     |                      | 0,75 mg/m <sup>3</sup> (Comsumer) |

(Contd. on page 5)

Trade name: **PEROXAN A-50 M**

(Contd. of page 4)

|  |                          |                                |
|--|--------------------------|--------------------------------|
| <b>123-54-6 pentane-2,4-dione</b>              |                          |                                |
| Dermal   | DNEL Longterm System     | 12 mg/kg bw/day (Worker)       |
| Inhalative                                     | DNEL Longterm System     | 84 mg/m <sup>3</sup> (Worker)  |
| <b>7722-84-1 hydrogen peroxide solution</b>    |                          |                                |
| Inhalative                                     | DNEL Longterm Local      | 1,4 mg/m <sup>3</sup> (Worker) |
| <b>· PNECs</b>                                 |                          |                                |
| <b>123-42-2 4-hydroxy-4-methylpentan-2-one</b> |                          |                                |
| PNEC Marinewater sed                           | 0,91 mg/kg sed dw        |                                |
| PNEC Freshwater                                | 2 mg/l (AF 50)           |                                |
| PNEC Freshwater sed                            | 9,06 mg/kg sed dw        |                                |
| PNEC Soil                                      | 0,63 mg/kg soil dw       |                                |
| PNEC STP                                       | 10 mg/l (AF 100)         |                                |
| PNEC Marinewater                               | 0,2 mg/l (AF 500)        |                                |
| <b>37187-22-7 2,4-Pentanedione, peroxide</b>   |                          |                                |
| PNEC Marinewater sed                           | 0,153 mg/kg sed dw (-)   |                                |
| PNEC Freshwater                                | 0,17 mg/l (AF 10)        |                                |
| PNEC Freshwater sed                            | 1,53 mg/kg sed dw (-)    |                                |
| PNEC Soil                                      | 0,2 mg/kg soil dw (-)    |                                |
| PNEC STP                                       | 6,2 mg/l (AF 10)         |                                |
| PNEC Marinewater                               | 0,017 mg/l (AF 100)      |                                |
| <b>75-91-2 tert-butyl hydroperoxide</b>        |                          |                                |
| PNEC Freshwater                                | 0,0015 mg/l (AF 1.000)   |                                |
| PNEC Seawater                                  | 0,00015 mg/l (AF 10.000) |                                |
| PNEC Water                                     | 0,015 mg/l (AF 100)      |                                |
| PNEC Freshwater sed                            | 0,00621 mg/kg sed dw (-) |                                |
| <b>123-54-6 pentane-2,4-dione</b>              |                          |                                |
| PNEC Marinewater sed                           | 0,191 mg/kg sed dw       |                                |
| PNEC Freshwater                                | 0,2 mg/l (AF 50)         |                                |
| PNEC Freshwater sed                            | 1,909 mg/kg sed dw       |                                |
| PNEC STP                                       | 1,32 mg/l (AF 10)        |                                |
| PNEC Marinewater                               | 0,02 mg/l (AF 500)       |                                |
| <b>7722-84-1 hydrogen peroxide solution</b>    |                          |                                |
| PNEC Marinewater sed                           | 0,047 mg/kg sed dw       |                                |
| PNEC Freshwater                                | 0,013 mg/l (AF 50)       |                                |
| PNEC Freshwater sed                            | 0,047 mg/kg sed dw       |                                |
| PNEC Soil                                      | 0,002 mg/kg soil dw      |                                |
| PNEC STP                                       | mg/l (AF 100)            |                                |
| PNEC Marinewater                               | 0,013 mg/l (AF 50)       |                                |

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.  
 Keep away from foodstuffs, beverages and feed.  
 Immediately remove all soiled and contaminated clothing  
 Wash hands before breaks and at the end of work.  
 Store protective clothing separately.  
 Do not inhale gases / fumes / aerosols.  
 Avoid close or long term contact with the skin.  
 Avoid contact with the eyes and skin.  
 Do not eat, drink, smoke or sniff while working.  
 Use skin protection cream for skin protection.  
 Be sure to clean skin thoroughly after work and before breaks.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.  
 Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.






Filter A2

(Contd. on page 6)

— MT —

Trade name: **PEROXAN A-50 M**

(Contd. of page 5)

|   |   |
|---|---|
| · <b>Protection of hands:</b>               | Only use chemical-protective gloves with CE-labelling of category III.<br> Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation |
| · <b>Material of gloves</b>                 | Protective gloves<br>The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.<br>Butyl rubber, BR<br>Fluorocarbon rubber (Viton)<br>Nitrile rubber, NBR<br>Neoprene      |
| · <b>Penetration time of glove material</b> | The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.   |
| · <b>Eye protection:</b>                    |  Tightly sealed goggles  |
| · <b>Body protection:</b>                   |  Protective work clothing  |

### SECTION 9: Physical and chemical properties

|   |   |
|---|---|
| · <b>9.1 Information on basic physical and chemical properties</b>        |   |
| · <b>General Information</b>  |   |
| · <b>Appearance:</b>  |   |
| · <b>Form:</b>  | Fluid   |
| · <b>Colour:</b>  | Colourless  |
| · <b>Odour:</b>   | Characteristic  |
| · <b>Odour threshold:</b>   | Not determined.   |
| · <b>pH-value:</b>  | Not determined.   |
| · <b>Change in condition</b>  |   |
| · <b>Melting point/freezing point:</b>                                    | Not applicable.   |
| · <b>Initial boiling point and boiling range:</b>                         | Not applicable.   |
| · <b>Flash point:</b>   | > SADT  |
| · <b>Flammability (solid, gas):</b>                                       | Not applicable.   |
| · <b>Decomposition temperature:</b>                                       | > +60 °C (SADT)   |
| · <b>Auto-ignition temperature:</b>                                       | Product is not selfigniting.  |
| · <b>Explosive properties:</b>  | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| · <b>Explosion limits:</b>  |   |
| · <b>Lower:</b>   | Not determined.   |
| · <b>Upper:</b>   | Not determined.   |
| · <b>Vapour pressure:</b>   | Not determined.   |
| · <b>Density at 20 °C:</b>  | 1,021 g/cm <sup>3</sup>   |
| · <b>Relative density</b>   | Not determined.   |
| · <b>Vapour density</b>   | Not determined.   |
| · <b>Evaporation rate</b>   | Not determined.   |
| · <b>Solubility in / Miscibility with</b>                                 |   |
| · <b>water:</b>   | Undetermined.   |
| · <b>Partition coefficient: n-octanol/water:</b> not determined           |   |
| · <b>Viscosity:</b>   |   |
| · <b>Dynamic at 20 °C:</b>  | 15 mPas   |
| · <b>Kinematic:</b>   | Not determined.   |
| · <b>9.2 Other information</b> No further relevant information available. |   |
| · <b>Active oxygen</b>  | 5,1 - 5,3 %   |

### SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.

(Contd. on page 7)

Trade name: **PEROXAN A-50 M**

(Contd. of page 6)

- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous self-accelerating decomposition reaction and, under certain circumstances, explosion or fire can be caused by decomposition at and above the temperature. Contact with incompatible substances can cause decomposition at or below the SADT.  
No decomposition if used and stored according to specifications.  
To avoid thermal decomposition do not overheat.
- **10.3 Possibility of hazardous reactions** Self-accelerating decomposition at SADT.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).
- **10.6 Hazardous decomposition products:** Hydrocarbons, carbon dioxide and -monoxid.  
No hazardous decomposition products if used and stored according to specifications.
- **Additional information:** Emergency procedures will vary depending on conditions. The customer should have an emergency response plan in place.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Harmful if inhaled.

· **LD/LC50 values relevant for classification:**

**123-42-2 4-hydroxy-4-methylpentan-2-one**

|        |      |                            |
|--------|------|----------------------------|
| Oral   | LD50 | 2.520 mg/kg (rattus)       |
| Dermal | LD50 | 13.630 mg/kg (cuniculosus) |

**37187-22-7 2,4-Pentanedione, peroxide**

|        |      |                       |
|--------|------|-----------------------|
| Oral   | LD50 | >2.000 mg/kg (rattus) |
| Dermal | LD0  | >2.000 mg/kg (rattus) |

**75-91-2 tert-butyl hydroperoxide**

|            |           |                         |
|------------|-----------|-------------------------|
| Oral       | LD50      | 560 mg/kg (rattus)      |
| Dermal     | LD50      | 440 mg/kg (cuniculosus) |
| Inhalative | LC50 / 4h | 1,85 mg/l (rattus)      |

**123-54-6 pentane-2,4-dione**

|            |           |                    |
|------------|-----------|--------------------|
| Oral       | LD50      | 575 mg/kg (rattus) |
| Dermal     | LD50      | 790 mg/kg (rattus) |
| Inhalative | LC50 / 4h | 5,1 mg/l (rattus)  |

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes severe skin burns and eye damage.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Suspected of causing genetic defects.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- **12.1 Toxicity**

· **Aquatic toxicity:**

**75-91-2 tert-butyl hydroperoxide**

|            |                                      |
|------------|--------------------------------------|
| EC50 / 72h | 2,1 mg/l (selenastrum capricornutum) |
| LC50 / 96h | 42,3 mg/l (pimephales promelas)      |
| EC50       | 24,3 mg/l (activa sludge)            |
| EC50 / 48h | 20 mg/l (daphnia magna)              |

(Contd. on page 8)




Trade name: **PEROXAN A-50 M**

(Contd. of page 7)



|  |  |
|--|--|
| <b>123-54-6 pentane-2,4-dione</b>                |  |
| LC50 / 96h                                       | 72 mg/l (oncorhynchus mykiss)  |
| EC50 / 48h                                       | 75 mg/l (daphnia magna)  |
| · <b>12.2 Persistence and degradability</b>      | No further relevant information available.   |
| · <b>12.3 Bioaccumulative potential</b>          | No further relevant information available.   |
| · <b>12.4 Mobility in soil</b>                   | No further relevant information available.   |
| · <b>Ecotoxicological effects:</b>               |  |
| · <b>Remark:</b>                                 | Harmful to fish  |
| · <b>Additional ecological information:</b>      |  |
| · <b>General notes:</b>                          | Harmful to aquatic organisms<br>Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water<br>Do not allow product to reach ground water, water course or sewage system, even in small quantities.<br>Danger to drinking water if even extremely small quantities leak into the ground. |
| · <b>12.5 Results of PBT and vPvB assessment</b> |  |
| · <b>PBT:</b>                                    | Not applicable.  |
| · <b>vPvB:</b>                                   | Not applicable.  |
| · <b>12.6 Other adverse effects</b>              | No further relevant information available.   |

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**

|   |  |
|---|--|
|  | After diluting with a suitable desentisation agent to 10 %, the solution must be supplied to a special treatment (e. g. thermal utilization) under observance of all official regulations. |
|   | Must not be disposed together with household garbage. Do not allow product to reach sewage system.   |
- **Waste disposal key:** Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-number.
- **Uncleaned packaging:**
- **Recommendation:** This material and its container must be disposed of as hazardous waste.

### SECTION 14: Transport information

|   |   |
|---|---|
| · <b>14.1 UN-Number</b><br>· <b>ADR, IMDG, IATA</b>   | UN3105  |
| · <b>14.2 UN proper shipping name</b><br>· <b>ADR</b><br>· <b>IMDG, IATA</b>  | UN3105 ORGANIC PEROXIDE TYPE D, LIQUID (ACETYL ACETONE PEROXIDE)<br>ORGANIC PEROXIDE TYPE D, LIQUID (ACETYL ACETONE PEROXIDE) |
| · <b>14.3 Transport hazard class(es)</b><br>· <b>ADR</b>  |   |
|    |   |
| · <b>Class</b><br>· <b>Label</b>  | 5.2 (P1) Organic peroxides.<br>5.2  |
| · <b>IMDG, IATA</b>   |   |
|    |   |
| · <b>Class</b><br>· <b>Label</b>  | 5.2 Organic peroxides.<br>5.2   |
| · <b>14.4 Packing group</b><br>· <b>ADR, IMDG, IATA</b>   | Void  |
| · <b>14.5 Environmental hazards:</b><br>· <b>Marine pollutant:</b>  | No  |
| · <b>14.6 Special precautions for user</b><br>· <b>Hazard identification number (Kemler code):</b><br>· <b>Stowage Category</b> | Warning: Organic peroxides.<br>-<br>D   |

(Contd. on page 9)





Trade name: **PEROXAN A-50 M**

(Contd. of page 9)

Muta. 2: Germ cell mutagenicity – Category 2  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2  
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· \* Data compared to the  
previous version altered.

— MT —