

Printing date 27.03.2020 Version: 5 Revision: 23.03.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

• Trade name: PEROXAN PND-75

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance /

the mixture

Reaction initiator For industrial use

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: PER

PERGAN GmbH

Hilfsstoffe für industrielle Prozesse

Schlavenhorst 71 D-46395 Bocholt Tel: +49 2871 9902-0 Fax: +49 2871 9902-50

· Further information obtainable

from:

Environment protection / Security of labour

Competent person:

* Sales Manager Germany: Mr. Ansgar Pappenheim, e-mail: a.pappenheim@pergan.com * Export Sales Manager: Mr. Dr. Thomas Philipps, e-mail: dr.philipps@pergan.com

* Environment protection / : Mr. Christoph Wilting, e-mail: c.wilting@pergan.com Security of labour

· 1.4 Emergency telephone

number:

- Tel: +49 2871 9902-0

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.
Org. Perox. D H242 Heating may cause a fire.
Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.

2.2 Label elements

· Labelling according to

Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms









· Signal word

Danger

· Hazard-determining components of labelling:

tert-butyl peroxyneodecanoate

Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated

· Hazard statements

H226 Flammable liquid and vapour. H242 Heating may cause a fire. H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H304 May be fatal if swallowed and enters airways. H410 Very toxic to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P220 Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and

accelerators (e. g. heavy metal compounds and amines).

P234 Keep only in original packaging.
P243 Take action to prevent static discharges.
P264 Wash thoroughly after handling.
P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

(Contd. on page 2)



(Contd. of page 1)

Printing date 27.03.2020 Version: 5 Revision: 23.03.2020

Trade name: PEROXAN PND-75

P410 Protect from sunlight.

Store at temperatures not exceeding 0°C. Keep cool.

P411+P235 P420 Do not mix with peroxide-accelerators or reducing agents. Dispose of contents/container in accordance with local/regional/national/international P501

regulations.

· 2.3 Other hazards

Results of PBT and vPvB assessment

Not applicable. · PBT: · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Dangerous components:				
CAS: 26748-41-4	tert-butyl peroxyneodecanoate	70-80%		
EINECS: 247-955-1	Org. Perox. D. H242; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; Skin Sens.			
Reg-No.: 01-2119948628-22	1, H317			
CAS: 93685-81-5	Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated	20-25%		
EINECS: 297-629-8	Alternative CAS number: 13475-82-6			
Reg-No.: 01-2119490725-29	Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 4, H413			

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information:

Take care of personal protection for the first aider.

· After inhalation: Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Take affected persons into fresh air and keep quiet.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

Immediately remove contaminated clothing.

After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist consult doctor.

· After swallowing:

· 4.2 Most important symptoms

and effects, both acute and

delayed 4.3 Indication of any immediate

medical attention and special

treatment needed

No further relevant information available.

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.

· For safety reasons unsuitable extinguishing agents:

Water with full jet 5.2 Special hazards arising from

the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded.

Hydrocarbons, carbondioxide and -monoxid.

5.3 Advice for firefighters

· Protective equipment: Do not inhale explosion gases or combustion gases.

Additional information Cool endangered receptacles with water spray.

Self-protection first!

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

In case of further temperature should be cooled with waterspray from a safe distance.

Wear breathing apparatus with filter A during decomposition of materials.

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 3)



Printing date 27.03.2020 Version: 5 Revision: 23.03.2020

Trade name: PEROXAN PND-75

Inform respective authorities in case of seepage into water course or sewage system. · 6.2 Environmental precautions:

(Contd. of page 2)

· 6.3 Methods and material for containment and cleaning up: Do not allow to enter sewers/ surface or ground water.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Large quantities should be diluted with suitable desensitation agent to a concentration below 10 % before

disposal.

Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government

regulations.

· 6.4 Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

In case of large spillage the environmental authority should be informed.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep receptacles tightly sealed.

Store in cool, dry place in tightly closed receptacles.

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Do not refill residue into storage receptacles. Restrict the quantity stored at the work place.

Use only in well ventilated areas.

Before break and at the end of work hands should be thoroughly washed. Only use tools made of suitable materials (e. g. polyethylene or stainless steel).

Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-

metal compounds and amines). Avoid contact with skin and eyes. While using do not eat, drink or smoke.

Do not generate flames or sparks.

Keep product and emptied container away from heat and sources of ignition.

Avoid shock and friction.

Take precautionary measures against static discharges.



Do not smoke.

· Information about fire - and explosion protection:

Protect from heat.

Protect against electrostatic charges.

Prevent impact and friction

Use explosion-proof apparatus / fittings and spark-proof tools. Fumes can combine with air to form an explosive mixture.



Wear shoes with conductive soles.

Formation of flammable or explosive gas/air-mixtures is possible.



Avoid open flames, sparks, direct sunlight and other sources of ignition.

Keep ignition sources away - Do not smoke.

· 7.2 Conditions for safe storage, including any incompatibilities

Requirements to be met by

· Storage:

Pay attention to the special requirements of your local autorithies for storing dangerous goods.

storerooms and receptacles:

Store in a cool location.

Store only in the original receptacle. Prevent any seepage into the ground.

Use only receptacles specifically permitted for this substance/product.

· Information about storage in one common storage facility:

Do not store or park organic peroxide together with heavy metal compounds and amines.

Store away from foodstuffs, drinks and feeding stuffs.

Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 4)



(Contd. of page 3)

Printing date 27.03.2020 Version: 5 Revision: 23.03.2020

Trade name: PEROXAN PND-75

Protect from heat and direct sunlight.

Protect from contamination.

Store in a cool place.

Storage in a collecting room is required.

 Recommended storage temperature (To maintain

quality): max.: -10 °C Control temperature: 0 °C · Emergency temperature: +10 °C Storage class: 52

· 7.3 Specific end use(s) No further relevant information available

SECTION 8: Exposure controls/personal protection

· Additional information about

design of technical facilities: No further data: see item 7.

8.1 Control parameters Ingredients with limit values

that require monitoring at the

workplace: The product does not contain any relevant quantities of materials with critical values that have to be

monitored at the workplace.

· DNFI s

26748-41-4 tert-butyl peroxyneodecanoate

DNEL Longterm System 8 mg/kg bw/day (Worker) Inhalative DNEL Longterm System 2,8 mg/m3 (Worker)

· PNECs

26748-41-4 tert-butyl peroxyneodecanoate

PNEC Marinewater sed 0,219 mg/kg sed dw (-) PNEC Freshwater 0,005 mg/l (AF 10) PNEC Freshwater sed 2,19 mg/kg sed dw (-) PNEC Soil 0,434 mg/kg soil dw (-) PNEC STP 96,69 mg/l (AF 10) 0 mg/l (AF 100) **PNEC Marinewater**

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

· Personal protective equipment:

General protective and

hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid close or long term contact with the skin.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection.

Be sure to clean skin thoroughly after work and before breaks.

· Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer

exposure use self-contained respiratory protective device.

Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.



Filter A2

· Protection of hands: Only use chemical-protective gloves with CE-labelling of category III. Selection of the glove material on consideration of the penetration times, rates of diffusion and the

degradation

Protective gloves

· Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of

quality and varies from manufacturer to manufacturer.

Butyl rubber, BR

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

Neoprene

Penetration time of glove

material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be

observed

(Contd. on page 5)



Printing date 27.03.2020 Version: 5 Revision: 23.03.2020

Trade name: PEROXAN PND-75

· Eye protection:

(Contd. of page 4)

· Body protection:

Tightly sealed goggles Protective work clothing

Not determined.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties
· General Information

Appearance:

· pH-value:

· Form: Fluid Colourless · Colour: · Odour: Characteristic · Odour threshold: Not determined.

· Change in condition

Melting point/freezing point: Not applicable. · Initial boiling point and boiling range: Not applicable.

· Flash point: > SADT · Flammability (solid, gas): Not applicable.

· Decomposition temperature: +20 °C (SADT) · Auto-ignition temperature: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

· Lower: Not determined · Upper: Not determined. · Vapour pressure: Not determined.

· Density at 20 °C: 0,87 g/cm3 Not determined. · Relative density Not determined. · Vapour density · Evaporation rate Not determined.

· Solubility in / Miscibility with

Undetermined.

· Partition coefficient: n-octanol/water: not determined

· Viscosity:

Dynamic: Not determined. Kinematic: Not determined

9.2 Other information No further relevant information available.

· Active oxygen 4,8 - 5,0 %

SECTION 10: Stability and reactivity

· 10.1 Reactivity

10.2 Chemical stability

No further relevant information available.

· Thermal decomposition / conditions to be avoided:

SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous selfaccelerating decomposition reaction and, under certain circumstances, explosion or fire can be cause decomposition at and above the temperature. Contact with incompatible substances can cause

decomposition at or below the SADT. No decomposition if used and stored according to specifications.

To avoid thermal decomposition do not overheat.

· 10.3 Possibility of hazardous

reactions

Self-accelerating decomposition at SADT. No further relevant information available.

· 10.4 Conditions to avoid · 10.5 Incompatible materials:

Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g.

heavy-metal compounds and amines).

(Contd. on page 6)



(Contd. of page 5)

Printing date 27.03.2020 Version: 5 Revision: 23.03.2020

Trade name: PEROXAN PND-75

· 10.6 Hazardous decomposition products:

Hydrocarbons, carbondioxide and -monoxid.

No hazardous decomposition products if used and stored according to specifications.

 Additional information: Emergency procedures will vary depending on conditions. The customer should have an emergency

response plane in place.

SECTION 11: Toxicological information

I D/I C50 values relevant for classifications

· 11.1 Information on toxicological effects

 Acute toxicity Based on available data, the classification criteria are not met.

LD/LC30 values relevant for classification.				
26748-41-4 tert-butyl peroxyneodecanoate				
Oral	LD50	10.776 mg/kg (rattus)		
Dermal	LD50	>6.000 mg/kg (cuniculosus)		
Inhalative	LC50 / 4h	37,5 mg/l (rattus)		

93685-81-5 Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated

Oral LD50 >5.000 mg/kg (rattus)

Primary irritant effect:

· Skin corrosion/irritation Causes skin irritation.

· Serious eye damage/irritation Based on available data, the classification criteria are not met.

· Respiratory or skin

sensitisation May cause an allergic skin reaction. CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

· Germ cell mutagenicity Based on available data, the classification criteria are not met. Carcinogenicity Based on available data, the classification criteria are not met. Reproductive toxicity Based on available data, the classification criteria are not met. · STOT-single exposure Based on available data, the classification criteria are not met. STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard May be fatal if swallowed and enters airways

SECTION 12: Ecological information

· 12.1 Toxicity

Aquatic toxicity:

26748-41-4 tert-butyl peroxyneodecanoate

LC50 / 96h 0,33 mg/l (brachydanio rerio) EC50 / 48h 0,79 mg/l (daphnia magna)

93685-81-5 Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated

EC50 / 48h | >0,04 mg/l (daphnia) IC50 / 72h |>0,04 mg/l (alga)

12.2 Persistence and

No further relevant information available. degradability No further relevant information available. 12.3 Bioaccumulative potential · 12.4 Mobility in soil No further relevant information available. Ecotoxical effects:

Harmful to fish · Remark:

Additional ecological information:

General notes: Harmful to aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

· 12.5 Results of PBT and vPvB assessment · PBT: Not applicable.

Not applicable. · 12.6 Other adverse effects No further relevant information available

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

Recommendation

· vPvB:



After diluting with a suitable desentisation agent to 10 %, the solution must be supplied to a special treatment (e.g. thermal utilization) under observance of all official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage

(Contd. on page 7)



Printing date 27.03.2020 Version: 5 Revision: 23.03.2020

Trade name: PEROXAN PND-75

(Contd. of page 6)

• Waste disposal key: Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-

number.

· Uncleaned packaging:

• **Recommendation:** This material and its container must be disposed of as hazardous waste.

SECTION 14: Transport information	
· 14.1 UN-Number	
· ADR, IMDG	UN3115
· 14.2 UN proper shipping name · ADR · IMDG	UN3115 ORGANIC PEROXIDE TYPE D, LIQUID, TEMPERATURE CONTROLLED (tert-BUTYL PEROXYNEODECANOATE), ENVIRONMENTALLY HAZARDOUS ORGANIC PEROXIDE TYPE D, LIQUID, TEMPERATURE CONTROLLED (tert-BUTYL PEROXYNEODECANOATE), MARINE
	POLLUTANT
· 14.3 Transport hazard class(es)	
· ADR	
1 1 1 1 1 1 1 1 1 1	
· Class · Label	5.2 (P2) Organic peroxides. 5.2
·IMDG	5.2
TIMIDG	
· Class · Label	5.2 Organic peroxides.5.2
· IATA	v
· Class · Label	X X
· 14.4 Packing group	··
ADR, IMDG	Void
· 14.5 Environmental hazards:	Product contains environmentally hazardous substances: tert-BUTYL
· Marine pollutant:	PEROXYNEODECANOATE Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Organic peroxides.
Hazard identification number (Kemler code): Stowage Category	- D
Stowage Code	SW1 Protected from sources of heat.
· Segregation Code	SW3 Shall be transported under temperature control. SG35 Stow "separated from" SGG1-acids
	SG36 Stow "separated from" SGG18-alkalis.
 14.7 Transport in bulk according to Annex II of Marpo IBC Code 	ol and the Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	0
Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
Transport category Tunnel restriction code	1 D
· RID / GGVSEB:	no admission
·IMDG	
Limited quantities (LQ) Excepted quantities (EQ)	0 Code: E0 Not permitted as Excepted Quantity

Not permitted as Excepted Quantity

(Contd. on page 8)



Printing date 27.03.2020 Version: 5 Revision: 23.03.2020

Trade name: PEROXAN PND-75

(Contd. of page 7)

·IATA Remarks: no admission · Control temperature: 0°C +10 °C · Emergency temperature:

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances

- ANNEX I None of the ingredients is listed.

P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES Seveso category

E1 Hazardous to the Aquatic Environment

Qualifying quantity (tonnes) for the application of lower-tier requirements 50 t

Qualifying quantity (tonnes) for the application of upper-tier

requirements **REGULATION (EC) No**

200 t

1907/2006 ANNEX XVII Conditions of restriction: 3

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: Environment protection / Security of labour

· Contact: Tel: +49 2871 9902-0 E-mail: mail@pergan.com

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage

of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
org. Perox. D: Organic peroxides – Type C/D
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4

·* Data compared to the previous version altered.

МТ