

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name: **PEROXAN PO**

CAS Number: 3006-82-4  
EC number: 221-110-7  
Registration number: 01-2119498310-40

1.2 Relevant identified uses of the substance or mixture and uses advised against  
No further relevant information available.

Application of the substance / the mixture  
Reaction initiator  
For industrial use

### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: PERGAN GmbH  
Hilfsstoffe für industrielle Prozesse  
Schlavenhorst 71  
D-46395 Bocholt  
Tel: +49 2871 9902-0  
Fax: +49 2871 9902-50

Further information obtainable from:

Environment protection / Security of labour  
Competent person:

\* Sales Manager Germany: Mr. Ansgar Pappenheim, e-mail: a.pappenheim@pergan.com  
\* Export Sales Manager: Mr. Dr. Thomas Philipps, e-mail: dr.philipps@pergan.com  
\* Environment protection / : Mr. Christoph Wiltung, e-mail: c.wiltung@pergan.com  
Security of labour

1.4 Emergency telephone number:

- Tel: +49 2871 9902-0

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Org. Perox. C H242 Heating may cause a fire.  
Skin Sens. 1 H317 May cause an allergic skin reaction.  
Repr. 2 H361f Suspected of damaging fertility.  
Aquatic Acute 1 H400 Very toxic to aquatic life.  
Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.

### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008  
Hazard pictograms

The substance is classified and labelled according to the CLP regulation.



GHS02 GHS07 GHS08 GHS09

Signal word

Danger

Hazard-determining components of labelling:  
Hazard statements

tert-butyl 2-ethylperoxyhexanoate  
H242 Heating may cause a fire.  
H317 May cause an allergic skin reaction.  
H361f Suspected of damaging fertility.  
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P220 Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy metal compounds and amines).  
P234 Keep only in original container.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P308+P313 IF exposed or concerned: Get medical advice/attention.  
P391 Collect spillage.  
P410 Protect from sunlight.  
P411+P235 Store at temperatures not exceeding +20°C. Keep cool.  
P420 Do not mix with peroxide-accelerators or reducing agents.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

### 2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.  
vPvB: Not applicable.

Trade name: **PEROXAN PO**

(Contd. of page 1)

**SECTION 3: Composition/information on ingredients****3.1 Chemical characterisation: Substances**

- CAS No. Description 3006-82-4 tert-butyl 2-ethylperoxyhexanoate
- Identification number(s)
- EC number: 221-110-7

**SECTION 4: First aid measures****4.1 Description of first aid measures****General information:**

Take care of personal protection for the first aider.

- **After inhalation:** Take affected persons into fresh air and keep quiet.
- **After skin contact:** Immediately remove contaminated clothing.
- **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.

**4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

- **Suitable extinguishing agents:** CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

**5.2 Special hazards arising from the substance or mixture**

Under certain fire conditions, traces of other toxic gases cannot be excluded.  
Hydrocarbons, carbon dioxide and -monoxid.

**5.3 Advice for firefighters**

- **Protective equipment:** Do not inhale explosion gases or combustion gases.
- **Additional information** Cool endangered receptacles with water spray.  
Self-protection first!

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Remove persons from danger area.  
Keep away from ignition sources.  
After exceeding the emergency temperature must be diluted with a suitable desensitisation agent to < 10 %.  
In case of further temperature should be cooled with waterspray from a safe distance.  
Wear breathing apparatus with filter A during decomposition of materials.  
Wear protective equipment. Keep unprotected persons away.

**6.2 Environmental precautions:**

Do not allow to enter sewers/ surface or ground water.

**6.3 Methods and material for containment and cleaning up:**

Ensure adequate ventilation.  
Large quantities should be diluted with suitable desensitisation agent to a concentration below 10 % before disposal.  
Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government regulations.

**6.4 Reference to other sections**

See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.  
In case of large spillage the environmental authority should be informed.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

Keep receptacles tightly sealed.  
Keep away from heat and direct sunlight.  
Open and handle receptacle with care.  
Prevent formation of aerosols.

(Contd. on page 3)

Trade name: **PEROXAN PO**

(Contd. of page 2)

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.  
 Handle with care. Avoid jolting, friction and impact.  
 Do not refill residue into storage receptacles.  
 Restrict the quantity stored at the work place.  
 Before break and at the end of work hands should be thoroughly washed.  
 Only use tools made of suitable materials (e. g. polyethylene or stainless steel).  
 The product must be preserved, stored and transported continuously cool.  
 Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).  
 Oxidizing because of releasing oxygene.  
 Avoid contact with skin and eyes.  
 While using do not eat, drink or smoke.  
 Do not generate flames or sparks.  
 Keep product and emptied container away from heat and sources of ignition.  
 Avoid shock and friction.  
 Take precautionary measures against static discharges.



Do not smoke.

· **Information about fire - and explosion protection:**

Protect from heat.  
 Protect against electrostatic charges.  
 Prevent impact and friction.  
 Use explosion-proof apparatus / fittings and spark-proof tools.  
 Fumes can combine with air to form an explosive mixture.



Wear shoes with conductive soles.

Formation of flammable or explosive gas/air-mixtures is possible.



Avoid open flames, sparks, direct sunlight and other sources of ignition.

Keep ignition sources away - Do not smoke.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:** Pay attention to the special requirements of your local authorities for storing dangerous goods.

· **Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.  
 Prevent any seepage into the ground.  
 Use only receptacles specifically permitted for this substance/product.

· **Information about storage in one common storage facility:** Do not store or park organic peroxide together with heavy metal compounds and amines.  
 Store away from foodstuffs, drinks and feeding stuffs.

· **Further information about storage conditions:** Keep container tightly sealed.  
 Protect from heat and direct sunlight.  
 Protect from contamination.  
 Store under lock and key and with access restricted to technical experts or their assistants only.  
 Storage in a collecting room is required.

· **Recommended storage temperature (To maintain quality):** max.: +15°C

· **Control temperature:** +20°C

· **Emergency temperature:** +25°C

· **Storage class:** 5.2

· **7.3 Specific end use(s)** No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

· **Additional information about design of technical facilities:** No further data; see item 7.

· **8.1 Control parameters**  
 · **Ingredients with limit values that require monitoring at the workplace:** Not required.

· **DNELs**





**3006-82-4 tert-butyl 2-ethylperoxyhexanoate**

Dermal	DNEL Longterm System	1.8 mg/kg bw/day (Worker)
Inhalative	DNEL Longterm System	3.17 mg/m3 (Worker)

(Contd. on page 4)

Trade name: **PEROXAN PO**

(Contd. of page 3)

· <b>PNECs</b>	
<b>3006-82-4 tert-butyl 2-ethylperoxyhexanoate</b>	
PNEC Marinewater sed	0.0622 mg/kg sed dw
PNEC Freshwater	0.002 mg/l (AF 50)
PNEC Freshwater sed	0.622 mg/kg sed dw
PNEC STP	0.64 mg/l (AF 100)
PNEC Marinewater	0 mg/l (AF 500)
· <b>Additional information:</b>	The lists valid during the making were used as basis.
· <b>8.2 Exposure controls</b>	
· <b>Personal protective equipment:</b>	
· <b>General protective and hygienic measures:</b>	The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection. Be sure to clean skin thoroughly after work and before breaks.
· <b>Respiratory protection:</b>	Not necessary if room is well-ventilated. Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.
	 Filter A2
· <b>Protection of hands:</b>	Only use chemical-protective gloves with CE-labelling of category III. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
	 Protective gloves
· <b>Material of gloves</b>	The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. Butyl rubber, BR Fluorocarbon rubber (Viton) Nitrile rubber, NBR Neoprene
· <b>Penetration time of glove material</b>	The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
· <b>Eye protection:</b>	 Tightly sealed goggles
· <b>Body protection:</b>	 Protective work clothing

## SECTION 9: Physical and chemical properties

· <b>9.1 Information on basic physical and chemical properties</b>	
· <b>General Information</b>	
· <b>Appearance:</b>	
· <b>Form:</b>	Fluid
· <b>Colour:</b>	Colourless
· <b>Odour:</b>	Characteristic
· <b>Change in condition</b>	
· <b>Melting point/freezing point:</b>	Not applicable.
· <b>Initial boiling point and boiling range:</b>	Not applicable.
· <b>Flash point:</b>	> SADT
· <b>Decomposition temperature:</b>	+35 °C (SADT)
· <b>Explosive properties:</b>	Risk of explosion by shock, friction, fire or other sources of ignition.
· <b>Density at 20 °C:</b>	0.9 g/cm <sup>3</sup>
· <b>Solubility in / Miscibility with water:</b>	Undetermined.
· <b>Partition coefficient: n-octanol/water:</b>	not determined

(Contd. on page 5)

Trade name: **PEROXAN PO**

(Contd. of page 4)

· Viscosity:	
· Dynamic at 20 °C:	4 mPas
· 9.2 Other information	No further relevant information available.
· Active oxygen	> 7.2 %

**SECTION 10: Stability and reactivity**

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous self-accelerating decomposition reaction and, under certain circumstances, explosion or fire can be cause decomposition at and above the temperature. Contact with incompatible substances can cause decomposition at or below the SADT.  
No decomposition if used and stored according to specifications.  
To avoid thermal decomposition do not overheat.
- 10.3 Possibility of hazardous reactions Self-accelerating decomposition at SADT.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).
- 10.6 Hazardous decomposition products: Hydrocarbons, carbon dioxide and -monoxid.  
No hazardous decomposition products if used and stored according to specifications.
- Additional information: Emergency procedures will vary depending on conditions. The customer should have an emergency response plane in place.

**SECTION 11: Toxicological information**

- 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.

## · LD/LC50 values relevant for classification:

**3006-82-4 tert-butyl 2-ethylperoxyhexanoate**

Oral	LD50	>10,000 mg/kg (rattus)
Inhalative	LC50 / 4h	42.2 mg/l (rattus)

- Primary irritant effect:
- Skin corrosion/irritation Low irritant effect
- Serious eye damage/irritation Low irritant effect
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Suspected of damaging fertility.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

**SECTION 12: Ecological information**

## · 12.1 Toxicity

## · Aquatic toxicity:

**3006-82-4 tert-butyl 2-ethylperoxyhexanoate**

LC50 / 96h	8.66 mg/l (poecilia reticulata)
EC50 / 48h	7.5 mg/l (daphnia)

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes: Water hazard class 2 (German Regulation) (Assessment by list): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.


(Contd. on page 6)  
GB

Trade name: **PEROXAN PO**



(Contd. of page 5)

- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

### SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation  After diluting with a suitable desensitisation agent to 10 %, the solution must be supplied to a special treatment (e. g. thermal utilization) under observance of all official regulations.  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- Waste disposal key: Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-number.
- Uncleaned packaging:
- Recommendation: This material and its container must be disposed of as hazardous waste.

### SECTION 14: Transport information

· 14.1 UN-Number · ADR, IMDG	UN3113
· 14.2 UN proper shipping name · ADR  · IMDG	UN3113 ORGANIC PEROXIDE TYPE C, LIQUID, TEMPERATURE CONTROLLED (tert-BUTYLPEROXY-2-ETHYLHEXANOATE), ENVIRONMENTALLY HAZARDOUS ORGANIC PEROXIDE TYPE C, LIQUID, TEMPERATURE CONTROLLED (tert-BUTYLPEROXY-2-ETHYLHEXANOATE), MARINE POLLUTANT
· 14.3 Transport hazard class(es) · ADR  · Class · Label	5.2 (P2) Organic peroxides. 5.2
· IMDG  · Class · Label	5.2 Organic peroxides. 5.2
· 14.4 Packing group · ADR, IMDG	Void
· 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR):	Product contains environmentally hazardous substances: tert-BUTYLPEROXY-2-ETHYLHEXANOATE Yes Symbol (fish and tree) Symbol (fish and tree)
· 14.6 Special precautions for user · Danger code (Kemler): · Stowage Category · Stowage Code  · Segregation Code	Warning: Organic peroxides. - D SW1 Protected from sources of heat. SW3 Shall be transported under temperature control. SG35 Stow "separated from" SGG1-acids SG36 Stow "separated from" SGG18-alkalis.
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ)	0

(Contd. on page 7)  
GB

Trade name: **PEROXAN PO**

(Contd. of page 6)

· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	1
· Tunnel restriction code	D
· RID / GGVSEB:	no admission
· IMDG	
· Limited quantities (LQ)	0
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· IATA	
· Remarks:	no admission
· Control temperature:	+20°C
· Emergency temperature:	+25°C

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- Directive 2012/18/EU
- Qualifying quantity (tonnes) for the application of lower-tier requirements 50 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- National regulations:
- Other regulations, limitations and prohibitive regulations
- Please note: Take care of the respective local regulations.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: Environment protection / Security of labour
- Contact: Tel: +49 2871 9902-0  
E-mail: [mail@pergan.com](mailto:mail@pergan.com)
- Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
DNEL: Derived No-Effect Level (REACH)  
PNEC: Predicted No-Effect Concentration (REACH)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Org. Perox. C: Organic peroxides – Type C/D  
Skin Sens. 1: Skin sensitisation – Category 1  
Repr. 2: Reproductive toxicity – Category 2  
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1  
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

· \* Data compared to the previous version altered.